



Garbage Cart (For Collecting and Delivering Diapers)

DC-S

Load capacity 80 kg

Platform size 480 x 600 mm

Platform height 900 mm

Handle height 900 mm

Empty weight 19.4 kg



DC-S

*Rubber handle cover is reference use only.



DC-S in use at Kanazawa City Hospital.



DC-M (Special ordered size) in use at Jukoen, a welfare facility.

Medical Cart (Stable and Silent Type)

BC-S

Load capacity Top shelf: 10 kg / Bottom shelf: 10 kg

Platform size 455 x 580 mm

Platform height 1010 mm


Handle height 950 mm

Empty weight 23.0 kg



BC-S (Shock absorbing sockets type)

*Socket color is reference only.



Shock Absorbing Socket (SA-SO M12)
Excellent shock absorbing performance by special component parts resulting in smooth and silent moving.

Left: Caster with shock absorbing sockets
Right: Shock absorbing socket

Suitable Casters

for DC Twin wheeled casters with VPA-K wheels



Swivel Swivel with stopper

S type	LDA-VPA75K	LDA-VPA75K-FI
M type	LDA-VPA75K	LDA-VPA75K-FI

for BC Twin wheeled casters Bolt hole fitting type with VPA-K wheels



Swivel Swivel with stopper

S type	LMDA-VPA75K	LMDA-VPA75K-FI
--------	-------------	----------------

for HC Shock absorbing casters with WUW wheels



Swivel

HC type	SAJ-100WUW
---------	------------

*WWW/LW wheel types also available.
(Operating temperature of LW: -70°C~+50°C)

Serving Cart (With Electric Motor)

HC-24 <for 24 trays>

Load capacity 100 kg

Platform size 760 x 770 mm

Platform height 1230 mm

Handle height 950 mm

Empty weight 106 kg



HC-24



HC-24/ Operation panel

HC-36 <for 36 trays>

Load capacity 100 kg

Platform size 760 x 1150 mm

Platform height 1230 mm

Handle height 950 mm

Empty weight 116 kg



HC-36



Wheel with electric motor

Reference Number System

DC - S

Garbage cart

Size - S