

# Electrically Conductive Castors I

-Medium duty type(steel)-

## J Swivel castors

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Unit weight		Load capacity
										EUW	MCD	
J-75	75	32	36	103	82 × 82	63 × 63	9.5	10	22	0.63	0.57	120(1170)
J-100	100	35	43	144	95 × 95	71 × 71	11	12	35	1.14	1.09	180(1760)
J-130	130	42	53	177	108 × 108	80 × 80	11.5	20	40	2.07	1.95	250(2450)
J-150	150	45	56	198	120 × 120	90 × 90	11.5	20	45	2.46	2.42	300(2940)
J-200	200	45	56	250	140 × 140	112 × 112	11.5	20	58	4.33	4.16	400(3920)

※Color:Zinc Plated.

## JB Swivel with stopper(Right)

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Unit weight		Load capacity
										EUW	MCD	
JB-75	75	32	36	103	82 × 82	63 × 63	9.5	10	22	0.69	—	120(1170)
JB-100	100	35	43	144	95 × 95	71 × 71	11	12	35	1.25	—	180(1760)
JB-130	130	42	53	177	108 × 108	80 × 80	11.5	20	40	2.22	—	250(2450)
JB-150	150	45	56	198	120 × 120	90 × 90	11.5	20	45	2.63	—	300(2940)
JB-200	200	45	56	250	140 × 140	112 × 112	11.5	20	58	4.54	—	400(3920)

※Color:Zinc Plated.

## JB(L) Swivel with stopper(Left)

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Unit weight		Load capacity
										EUW	MCD	
JB-100(L)	100	35	43	144	95 × 95	71 × 71	11	12	35	1.25	—	180(1760)
JB-130(L)	130	42	53	177	108 × 108	80 × 80	11.5	20	40	2.22	—	250(2450)
JB-150(L)	150	45	56	198	120 × 120	90 × 90	11.5	20	45	2.63	—	300(2940)
JB-200(L)	200	45	56	250	140 × 140	112 × 112	11.5	20	58	4.54	—	400(3920)

※Color:Zinc Plated.

## K Fixed with stopper (Left)

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Unit weight		Load capacity
										EUW	MCD	
K-75	75	32	36	103	91 × 68	63 × 40	9.5	10	—	0.48	0.42	120(1170)
K-100	100	35	43	144	115 × 79	80 × 45	11	12	—	0.88	0.84	180(1760)
K-130	130	42	53	177	137 × 93	100 × 56	11.5	20	—	1.72	1.61	250(2450)
K-150	150	45	56	198	137 × 93	100 × 56	11.5	20	—	2.02	1.98	300(2940)
K-200	200	45	56	250	151 × 100	112 × 63	11.5	20	—	3.67	3.50	400(3920)

※Color:Zinc Plated.

## KB Fixed with stopper (Right)

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Unit weight		Load capacity
										EUW	MCD	
KB-75	75	32	36	103	91 × 68	63 × 40	9.5	10	—	0.54	—	120(1170)
KB-100	100	35	43	144	115 × 79	80 × 45	11	12	—	1.01	—	180(1760)
KB-130	130	42	53	177	137 × 93	100 × 56	11.5	20	—	1.89	—	250(2450)
KB-150	150	45	56	198	137 × 93	100 × 56	11.5	20	—	2.19	—	300(2940)
KB-200	200	45	56	250	151 × 100	112 × 63	11.5	20	—	3.87	—	400(3920)

※Color:Zinc Plated.

### KB(L) Fixed with stopper (Left)

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Unit weight		Load capacity
										EUW	MCD	
KB-100(L)	100	35	43	144	115 × 79	80 × 45	11	12	—	0.99	—	180(1760)
KB-130(L)	130	42	53	177	137 × 93	100 × 56	11.5	20	—	1.88	—	250(2450)
KB-150(L)	150	45	56	198	137 × 93	100 × 56	11.5	20	—	2.20	—	300(2940)
KB-200(L)	200	45	56	250	151 × 100	112 × 63	11.5	20	—	3.87	—	400(3920)

※Color:Zinc Plated.