

Directional Lock Castors –Swivel↔Fixed–

NJK Swivel castors

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Unit weight							Load capacity		
										W	SST	UW	EUW	WUW	WW LW	SPM	W SST WUW	UW EUW	SPM WW LW
NJK-130	130	42	56	188	112 × 112	75 × 75– 90 × 90	11 × 21.5	12	41	1.97	—	2.05	2.06	2.08	1.91	—	180(1760)	250(2450)	— 140(1370)
NJK-150	150	45	56	198	112 × 112	75 × 75– 90 × 90	11 × 21.5	12	41	2.16	2.20	2.32	2.31	2.32	2.14	2.21	200(1960)	300(2940)	80(780) 160(1560)
NJK-200	200	45	62	250	140 × 140	100 × 100– 115 × 115	11.5 × 22	12	58	3.54	3.52	4.08	4.14	4.13	3.49	3.57	250(2450)	400(3920)	100(980) 200(1960)

※Color: Zinc plated

NJKB Swivel with stopper

	Wheel diameter	Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Unit weight							Load capacity		
										W	SST	UW	EUW	WUW	WW LW	SPM	W SST WUW	UW EUW	SPM WW LW
NJKB-130	130	42	56	188	112 × 112	75 × 75– 90 × 90	11 × 21.5	12	41	2.15	—	2.23	2.24	2.26	2.09	—	180(1760)	250(2450)	— 140(1370)
NJKB-150	150	45	56	198	112 × 112	75 × 75– 90 × 90	11 × 21.5	12	41	2.34	2.38	2.50	2.49	2.50	2.32	2.39	200(1960)	300(2940)	80(780) 160(1560)
NJKB-200	200	45	62	250	140 × 140	100 × 100– 115 × 115	11.5 × 22	12	58	3.73	3.71	4.27	4.33	4.32	3.68	3.76	250(2450)	400(3920)	100(980) 200(1960)

※Color: Zinc plated