Compact Medium Duty Castors

RoHS compliant products.

POINT

- CHJ and CHK have common bolt hole spacing.
- 3 types of top plates for swivel castors available according to fitting conditions.
- Available with MC (Monomer cast nylon/blue) and MCMO (Black MC) as optional items.
- Wheel with grease sealed precision radial ball bearings.
- Smooth and silent rolling without subsequent lubrication. NB CYN for swivel with stopper comes with needle bearing.

USE EXAMPLE

- For fixed precision machines to be occasionally relocated in a workplace, or moved as production line is rearranged.
- For medium duty slow-moving carriers.

CHJBN-65

CHJBN-75

See P.62 to P.71 for detailed description.

@We'll accept your custom-order. Please feel free to contact us. (Use "Specification Form for Custom-designed castor" at the end of this catalog.) OPlease feel free to ask about the product weight for each item.









WHEELS JBB ···Radial ball bearing NB ···Needle bearing

CHJN-65

CHJN-75

CHJ-75B-CYN









NB For details refer to the table below.

Compact Medium Duty

Refer to the page indicated below for other types of compact

Single wheeled castors

100kg∼500kg → P.19

→ P.23

Twin wheeled castors


1000kg **≟** 300kg∼500kg \rightarrow P.9 (Silent Smooth Castors \mathbb{I}), 21


Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Load capacity
→ mm	₩mm	<u></u>			0 0 0 mm	T mm	mm	kg(N)
45	52 \langle 46 \rangle *	90	105×80	81×59	11×9	10	23	250 (2450)
46	52 \langle 46 \rangle *	100	105×80	81×59	11×9	10	24	320 (3130)
*〈 〉Swivel with stopper								
Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Load capacity
		₹		I ⇔ I ○ ○ □	0 0	月	#	7
→]	l ⇔ l			0 0	0 0		(6)	
mm	mm	mm -	-	mm	mm	mm	mm	kg (N)
45	52 (46)*	orry, t	neseiite	ms are n	oteavall	abie any	more.	250 (2450)
46	52 (46)*	100	100 × 100	63×63-78×78	10.5×21	10	24	320 (3130)
*()Swivel with stopper								
Whice width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Load capacity
\cap		√∃₹	← → ○ ○ ↑	I ⇔ I ○ ○ <mark>⊼</mark>		77		7
→\\-	l⇔l	(V) Į	0 0		0 0			
mm	mm	mm	mm	mm	mm	mm	mm	kg (N)
45	52 (46)*	90	90×90	71×71	10.5	10	23	250 (2450)
46	52 (46)*	100	90×90	71×71	10.5	10	24	320 (3130)
*〈 〉Swivel with stopper								
Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter		Load capacity
		<u> </u>	< → ○ ○ ↑	↔	0 0	7		2
→U←	U	U Ţ	0 0	o o <u>₹</u>	0 0			
mm	mm		mm	mm	mm	mm and a second		kg(N)
45	52	orry, tr	nese itel	ms_are_no	ot avalla	able•any	more	250 (2450)

Reference Number System



CHJB-75B-CYN





320 (3130)





CHJN Swivel castors