POINT

- Wheel with grease sealed precision radial ball bearings.
 Smooth and silent rolling without subsequent lubrication.
- Low noise during running.
- Reinforced structure in the swivel head.

USE EXAMPLE

- For various carriers.
- For reducing carrier's total weight.

We'll accept your custom-order. Please feel free to contact us.
 (Use "Specification Form for Custom-designed castor" at the end of this catalog.)
 Please feel free to ask about the product weight for each item.



Reference Number System



Plastic Castors







NΒ	For	details	refer	to	the	table	below

PJ Swivel castors	$\overline{\overline{U}}$		
PJ-100			

PK Fixed castors	$\overline{\bigcup}$		
PK-100			
PK-130			

Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Load capacity
→ mm	mm mm				O O O	T T	™	kg (N)
32	44	144	95×95	71×71	11	12	30	100 (980)
38	53	177	108×108	80×80	11	12	35	145 (1420)

Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	 Load capacity
32	44	144	115×80	80×45	11	12	 100 (980)
38	53	177	137×93	100×50- 100×58	11	12	 145 (1420)

See P.62 to P.71 for detailed description.



PW (SBR)





.1