

Twin Wheeled Compact Heavy Duty Casters

HJT Swivel casters



HJT-50

HJT-65

HJT-75

• Color: Zinc plated with Cr III/White coating/Black coating/Chromium plated

HJTB Swivel with stopper



HJTB-50

HJTB-65

HJTB-75

HJT-SJ Threaded stem fitting



HJT-SJ-50

HJT-SJ-65

HJT-SJ-75

• Color: Zinc plated with Cr III/Black coating

HJTB-SJ Threaded stem fitting with stopper



HJTB-SJ-50

HJTB-SJ-65

HJTB-SJ-75

HKT Fixed casters



















































HKT-50

























HKT-65

HKT-75

• Color: Zinc plated with Cr III/White coating/Black coating

Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Load capacity
 15x2	 36	 78	 82x82	 55x55-65x65	 9.5x16.5	 8	 18	 300 (2940)
 17x2	 40	 96.5	 100x100	 63x63-78x78	 10.5x21	 10	 22	 400 (3920)
 18.5x2	 43	 108	 100x100	 63x63-78x78	 10.5x21	 10	 25	 500 (4900)

Wheel width	Hub length	Total height	Stem size	Axle bore diameter	Offset	Load capacity
 15x2	 36	 85	 M20x50xP2.5	 8	 18	 300 (2940)
 17x2	 40	 103	 M20x50xP2.5	 10	 22	 400 (3920)
 18.5x2	 43	 115	 M24x55xP3.0	 10	 25	 500 (4900)

Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Load capacity
 15x2	 36	 78	 85x58	 55x28	 9.5	 8	 300 (2940)
 17x2	 40	 96.5	 86x59	 55x28	 10.5	 10	 400 (3920)
 18.5x2	 43	 108	 95x72	 63x40	 10.5	 10	 500 (4900)