

Shock Absorbing Casters I -Center spring type- Patent No. 3689482

Traveling speed up to 4km/h

Towing speed up to 10km/h

SAJ Swivel casters



SAJ-100

SAJ-150

SAJ-200

SAJB Swivel with stopper



SAJB-100

SAJB-150

SAJB-200

NB Designed for traveling seed up to 4km/h.
Please consult us as special order if used at higher speed.

SAJ-HO Swivel casters

Towing speed up to 10km/h



SAJ-HO-150 (W, SST only)

SAJ-HO-200 (W, SST only)

• Color: Zinc plated

NB Designed for traveling seed up to 10km/h.
Please consult us as special order if used at higher speed.

SAK Fixed casters



SAK-100

SAK-150

SAK-200

SAKB Fixed with stopper



SAKB-100

SAKB-150

SAKB-200

NB Designed for traveling seed up to 4km/h.
Please consult us as special order if used at higher speed.

SAK-HO Fixed casters

Towing speed up to 10km/h



SAK-HO-150 (W, SST only)

SAK-HO-200 (W, SST only)

• Color: Zinc plated

NB Designed for traveling seed up to 10km/h.
Please consult us as special order if used at higher speed.

Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Spring tension	Load capacity		
mm	mm	mm	mm	mm	mm	mm	mm	kg	WW kg (N)	W SST LW MC kg (N)	SPM kg (N)
35	43	153-145	95x95	71x71	11	12	28.5-35	10-60	80 (780)	100 (980)	—
45	56	210-198	120x120	90x90	11.5	20	35-48	20-110 other than SPM 20-80 SPM	150 (1470)	150 (1470)	80 (780)
45	56	260-250	140x140	112x112	11.5	20	46.5-58	20-220 other than SPM 20-100 SPM	200 (1960)	250 (2450)	100 (980)
45	56	250-235	140x140	112x112	11.5	20	51-64	20-120	—	150 (1470)	—
45	56	275-260	140x140	112x112	11.5	20	51-64	20-180	—	200 (1960)	—

Wheel width	Hub length	Total height	Plate dimensions	Bolt hole spacing	Bolt hole diameter	Axle bore diameter	Offset	Spring tension	Load capacity		
mm	mm	mm	mm	mm	mm	mm	mm	kg	WW kg (N)	W SST LW MC kg (N)	SPM kg (N)
35	43	153-145	104x80	80x45	11	12	28.5-35	10-60	80 (780)	100 (980)	—
45	56	210-198	126x93	100x56	11.5	20	35-48	20-110 other than SPM 20-80 SPM	150 (1470)	150 (1470)	80 (780)
45	56	260-250	140x102	112x63	11.5	20	46.5-58	20-220 other than SPM 20-100 SPM	200 (1960)	250 (2450)	100 (980)
45	56	250-235	140x102	112x63	11.5	20	51-64	20-120	—	150 (1470)	—
45	56	275-260	140x102	112x63	11.5	20	51-64	20-180	—	200 (1960)	—